

Safety Data Sheet 50006

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 03/06/2015 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : Methane with Methyl Mercaptan (Methanethiol)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Test gas/Calibration gas.

1.3. Details of the supplier of the safety data sheet

Calgaz, division of Air Liquide 821 Chesapeake Drive Cambridge, 21613 - USA

T 1-410-228-6400 - F 1-410-228-4251 info@Calgaz.com - www.Calgaz.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 Internationally: 1-703-527-3887

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Gas 1 H220 Compressed gas H280

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



 \Diamond

02 GHS

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H220 - Extremely flammable gas

H280 - Contains gas under pressure; may explode if heated

Precautionary statements (GHS-US)

: P202 - Do not handle until all safety precautions have been read and understood P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely

P381 - Eliminate all ignition sources if safe to do so

P403 - Store in a well-ventilated place

P410+P403 - Protect from sunlight. Store in a well-ventilated place

P271 - Use only outdoors or in a well-ventilated area

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P313 - Get medical advice/attention

CGA-PG05 - Use a back flow preventive device in the piping

CGA-PG21 - Open valve slowly

CGA-PG06 - Close valve after each use and when empty CGA-PG10 - Use only with equipment rated for cylinder pressure

CGA-PG14 - Approach suspected leak area with caution

CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F)

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

Not applicable

03/06/2015 EN (English US) SDS ID: 50006 Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/information on ingredients

Substance

Not applicable

3.2. **Mixture**

Name	Product identifier	%	Classification (GHS-US)
Methane	(CAS No) 74-82-8	99.995	Flam. Gas 1, H220 Compressed gas, H280
Methanethiol	(CAS No) 74-93-1	0.005	Flam. Gas 1, H220 Liquefied gas, H280 Acute Tox. 3 (Inhalation:gas), H331 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H-phrases: see section 16

SECTION 4: First aid measures

Description of first aid measures

First-aid measures after inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel

unwell, seek medical advice.

First-aid measures after skin contact First-aid measures after eye contact

First-aid measures after ingestion

: Adverse effects not expected from this product. Adverse effects not expected from this product.

Ingestion is not considered a potential route of exposure.

Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation Symptoms/injuries after skin contact : May displace oxygen and cause rapid suffocation. : Adverse effects not expected from this product. Adverse effects not expected from this product.

Symptoms/injuries after eye contact Symptoms/injuries after ingestion

Ingestion is not considered a potential route of exposure.

Symptoms/injuries upon intravenous

administration

: Not known.

: Adverse effects not expected from this product. Chronic symptoms

Indication of any immediate medical attention and special treatment needed

If you feel unwell, seek medical advice. If breathing is difficult, give oxygen.

SECTION 5: Firefighting measures

Extinguishing media 5.1.

Suitable extinguishing media

: Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media

: Do not use water jet to extinguish.

Special hazards arising from the substance or mixture

Fire hazard

: Extremely flammable gas.

Explosion hazard

May form flammable/explosive vapor-air mixture. Heat may build pressure, rupturing closed

containers, spreading fire and increasing risk of burns and injuries.

Reactivity

: None known.

Advice for firefighters

Firefighting instructions

: In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire.

Protection during firefighting

Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire fighters. Do not enter fire area without proper protective equipment, including respiratory

protection.

Specific methods

Exposure to fire may cause containers to rupture/explode. Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive re-ignition may occur. Extinguish any other fire. Continue water spray from protected position until container stays cool. Move containers away from the fire area if this can be done without risk.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

General measures : Ensure adequate ventilation.

For non-emergency personnel 6.1.1

Protective equipment

: Wear protective equipment consistent with the site emergency plan.

03/06/2015 EN (English US) SDS ID: 50006 2/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Emergency procedures

: Escape the danger area by the closest safe route. Close doors and windows of adjacent premises. Keep containers closed. Mark the danger area. Seal off low-lying areas. Keep upwind.

6.1.2. For emergency responders

Protective equipment

: Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire fighters. Equip cleanup crew with proper protection.

Emergency procedures

: Evacuate and limit access. Ventilate area. Remove ignition sources. Monitor concentration of released product. Consider the risk of potentially explosive atmospheres. Wear self-contained breathing apparatus when entering atmospheres of unknown contaminant concentration until proven to be safe.

6.2. Environmental precautions

Try to stop release if safe to do so.

6.3. Methods and material for containment and cleaning up

For containment

: Try to stop release if safe to do so.

Methods for cleaning up

: Dispose of this material and its container in accordance with local regulations.

6.4. Reference to other sections

See also Sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

: Pressurized container: Do not pierce or burn, even after use. Handle empty containers with care because residual vapors are flammable. Use equipment rated for cylinder pressure. In use, may form flammable vapor-air mixture. Close valve after each use and when empty.

Precautions for safe handling

: Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Use only non-sparking tools. Use only outdoors or in a well-ventilated area.

Safe handling of the gas receptacle

: Protect cylinders from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the cylinder contents. Keep container valve outlets clean and free from contaminants particularly oil and water.

Safe use of the product

The substance must be handled in accordance with good industrial hygiene and safety procedures. Only experienced and properly instructed persons should handle gases under pressure. Consider pressure relief device(s) in gas installations. Ensure the complete gas system was (or is regularily) checked for leaks before use. Do not smoke while handling product. Do not remove or deface labels provided by the supplier for the identification of the cylinder contents. Keep equipment free from oil and grease. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Assess the risk of potentially explosive atmospheres and the need for explosion-proof equipment. Keep away from ignition sources (including static discharges). Consider the use of only non-sparking tools. Consider the use of flash back arrestors.

Hygiene measures

: Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed.

Storage conditions

: Do not expose to temperatures exceeding 52°C (125°F). Keep container closed when not in use. Protect cylinder from physical damage. Store in well ventilated area.

Incompatible products Incompatible materials

: None known.: Air. Oxidizing materials.

7.3. Specific end use(s)

See Section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Methane with Methyl Mercaptan (Methanethiol)		
ACGIH	ACGIH TWA (ppm) 1000 ppm	
OSHA	Not applicable	
Methanethiol (74-93-1)		
Methanethiol (74-93-1)		
Methanethiol (74-93-1) ACGIH	ACGIH TWA (ppm)	0.5 ppm

03/06/2015 EN (English US) SDS ID: 50006 3/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methanethiol (74-93-1)	Methanethiol (74-93-1)	
OSHA OSHA PEL (Ceiling) (ppm) 10 ppm		10 ppm
Methane (74-82-8)		
ACGIH ACGIH TWA (ppm) 1000 ppm		1000 ppm
OSHA Not applicable		

8.2. Exposure controls

Appropriate engineering controls : Provide adequate general and local exhaust ventilation. Systems under pressure should be

regularly checked for leakages. Consider work permit system e.g. for maintenance activities. Ensure exposure is below occupational exposure limits. Oxygen detectors should be used

when asphyxiating gases may be released.

Hand protection : Wear working gloves when handling gas containers. 29 CFR 1910.138: Hand Protection.

Eye protection : Wear safety glasses with side shields. 29 CFR 1910.133: Eye and Face Protection.

Skin and body protection : Wear suitable protective clothing, e.g. - lab coats, coveralls or flame resistant clothing.

Respiratory protection : None necessary during normal and routine operations. See Sections 5 & 6.

Thermal hazard protection : None necessary during normal and routine operations.

Environmental exposure controls : Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for

specific methods for waste gas treatment.

Other information : Wear safety shoes while handling containers. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas

Appearance : Clear, colorless gas.

Molecular mass : Not applicable for gas-mixtures.

Color : Colorless

Odor : skunk-like;Garlic like.
Odor threshold : No data available

pH : Not applicable for gas-mixtures.

Relative evaporation rate (butyl acetate=1) : No data available

Relative evaporation rate (ether=1) : Not applicable to gas mixtures

Melting point : No data available Freezing point : No data available Boiling point : No data available Flash point : No data available Critical temperature : -82.59 °C

Auto-ignition temperature : No data available Decomposition temperature No data available See Sect. 2.1 & 2.2 Flammability (solid, gas) Vapor pressure Not applicable Vapor pressure at 50 °C No data available Critical pressure No data available Relative vapor density at 20 °C No data available Relative density No data available Relative density of saturated gas/air mixture : No data available Specific gravity / density : No data available

Relative gas density : Lighter or similar to air. Solubility : Water: 26 mg/l

Log Pow : Not applicable for gas mixtures
Log Kow : Not applicable for gas mixtures

Viscosity, kinematic : Not applicable
Viscosity, dynamic : Not applicable

Explosive properties : Without adequate ventilation formation of explosive mixtures may be possible.

03/06/2015 EN (English US) SDS ID: 50006 4/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Oxidizing properties : None.

Explosive limits : No data available

Other information 9.2.

Additional information : None.

SECTION 10: Stability and reactivity

10.1. Reactivity

None known.

10.2. **Chemical stability**

Stable under normal conditions.

Possibility of hazardous reactions

Can form explosive mixture with air.

Conditions to avoid

None under recommended storage and handling conditions (see section 7).

Incompatible materials

Oxidizing materials. Air.

Hazardous decomposition products

Under normal conditions of storage and use hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Information on toxicological effects

: Not classified Acute toxicity

Methane with Methyl Mercaptan (Methanethiol)	
LC50 inhalation rat (ppm)	820000 ppm/4h
ATE US (gases)	820000.000 ppmV/4h
Methanethiol (74-93-1)	
LD50 oral rat	109.6 mg/kg
LD50 dermal rat	> 84.8 mg/kg
LC50 inhalation rat (ppm)	675 ppm/4h
ATE US (oral)	109.600 mg/kg body weight
ATE US (gases)	675.000 ppmV/4h
Methane (74-82-8)	
LC50 inhalation rat (ppm)	820000 ppm/4h
Skin corrosion/irritation : Not classified	

pH: Not applicable for gas-mixtures.

Serious eye damage/irritation : Not classified

pH: Not applicable for gas-mixtures.

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated

exposure)

: Not classified

: Not classified Aspiration hazard

: May displace oxygen and cause rapid suffocation. Symptoms/injuries after inhalation Symptoms/injuries after skin contact : Adverse effects not expected from this product. Symptoms/injuries after eye contact : Adverse effects not expected from this product.

Symptoms/injuries after ingestion : Ingestion is not considered a potential route of exposure.

03/06/2015 EN (English US) SDS ID: 50006 5/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/injuries upon intravenous

administration

: Not known.

Chronic symptoms : Adverse effects not expected from this product.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Classification criteria are not met.

12.2. Persistence and degradability

Methane with Methyl Mercaptan (Methanethiol)	
Persistence and degradability	The substance is biodegradable. Unlikely to persist. No data available.
Methanethiol (74-93-1)	
Persistence and degradability	The substance is biodegradable. Unlikely to persist.
Methane (74-82-8)	
Persistence and degradability	The substance is biodegradable. Unlikely to persist. No data available.

12.3. Bioaccumulative potential

Methane with Methyl Mercaptan (Methanethiol)	
Log Pow	Not applicable for gas mixtures
Log Kow	Not applicable for gas mixtures
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.
Methanethiol (74-93-1)	
Log Pow	Not known.
Bioaccumulative potential	No data available.
Methane (74-82-8)	
Log Pow	Not applicable for gas mixtures
Log Kow	Not applicable for gas mixtures
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.

12.4. Mobility in soil

Methane with Methyl Mercaptan (Methanethiol)	
Mobility in soil	No data available.
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.
Methanethiol (74-93-1)	
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.
Methane (74-82-8)	
Mobility in soil	No data available.
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.

12.5. Other adverse effects

Effect on ozone layer : None.

Global warming potential [CO2=1] : 25

Effect on the global warming : Contains greenhouse gas(es) not covered by 842/2006/EC.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods

: Contact supplier if guidance is required. Do not discharge into areas where there is a risk of forming an explosive mixture with air. Waste gas should be flared through a suitable burner with flash back arrestor. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from local regulations or operating permits are not exceeded.

Waste disposal recommendations : Refer to

 $: \ \ \mbox{Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at www.cganet.com for more \\$

guidance on suitable disposal methods.

Additional information : None.

03/06/2015 EN (English US) SDS ID: 50006 6/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

In accordance with DOT

Transport document description : UN1954 Compressed gas, flammable, n.o.s. (Methane, Methyl mercaptan), 2.1

UN-No.(DOT) : UN195

Proper Shipping Name (DOT) : Compressed gas, flammable, n.o.s.

(Methane, Methyl mercaptan)

Department of Transportation (DOT) Hazard

Classes

: 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Hazard labels (DOT) : 2.1 - Flammable gas

DOT Symbols : G - Identifies PSN requiring a technical name

DOT Packaging Exceptions (49 CFR 173.xxx) : 306

DOT Packaging Non Bulk (49 CFR 173.xxx) : 302;305

DOT Packaging Bulk (49 CFR 173.xxx) : 314;315

DOT Quantity Limitations Passenger aircraft/rail : Forbidden

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg

CFR 175.75)

DOT Vessel Stowage Location

: E - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length, but is prohibited from carriage on passenger vessels in which the limiting number of passengers is exceeded.,D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger vessels in

which the limiting number of passengers is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Additional information

Other information

: No supplementary information available.

Special transport precautions

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers:
 Ensure there is adequate ventilation.
 Ensure that containers are firmly secured.
 Ensure cylinder valve is closed and not leaking.
 Ensure valve outlet cap nut or plug (where provided) is correctly fitted.

ADR

Transport document description : UN 1954, 2, (B/D)

Class (ADR) : 2 - Gases

Hazard identification number (Kemler No.) : 23 Classification code (ADR) : 1F

Orange plates :

23 1971

Tunnel restriction code (ADR) : B/D LQ : 0 Excepted quantities (ADR) : E0

Transport by sea

UN-No. (IMDG) : 1954

Proper Shipping Name (IMDG) : COMPRESSED GAS, FLAMMABLE, N.O.S.

Class (IMDG) : 2.1 - Flammable gases

03/06/2015 EN (English US) SDS ID: 50006 7/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Air transport

UN-No.(IATA) : 1954

Proper Shipping Name (IATA) : COMPRESSED GAS, FLAMMABLE, N.O.S.

Class (IATA) : 2

SECTION 15: Regulatory information

15.1. US Federal regulations

Methane with Methyl Mercaptan (Methanethiol)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Methanethiol (74-93-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on the United States SARA Section 302

SARA Section 302 Threshold Planning

Quantity (TPQ)

500

Methane (74-82-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

PARTADA	
Methane with Methyl Mercaptan (Methanethiol)	
Listed on the Canadian DSL (Domestic Sustances List)	
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas

Methanethiol (74-93-1) Listed on the Canadian DSL (Domestic Sustances List) WHMIS Classification Class A - Compressed Gas		
		s List)
		Class A - Compressed Gas
		Class B Division 1 - Flammable Gas
		Class D Division 1 Subdivision A. Vary taxis material squaing immediate and serious

Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects

Methane (74-82-8)

Listed on the Canadian DSL (Domestic Sustances List)

WHMIS Classification Class A - Compressed Gas
Class B Division 1 - Flammable Gas

EU-Regulations

Methane with Methyl Mercaptan (Methanethiol)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Methanethiol (74-93-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Methane (74-82-8)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Gas 1 H220 Compressed gas H280

Full text of H-phrases: see section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

15.2.2. National regulations

Methane with Methyl Mercaptan (Methanethiol)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

03/06/2015 EN (English US) SDS ID: 50006 8/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methanethiol (74-93-1)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Japanese Poisonous and Deleterious Substances Control Law

Listed on the Canadian IDL (Ingredient Disclosure List)

Methane (74-82-8)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

15.3. US State regulations

5.5. OS State regulations	
Methane with Methyl Mercaptan (Methanethiol)()	
State or local regulations	U.S Massachusetts - Right To Know List U.S New Jersey - Right to Know Hazardous Substance List U.S Pennsylvania - RTK (Right to Know) List

Methanethiol (74-93-1)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

Methane (74-82-8)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

SECTION 16: Other information

Indication of changes : Revised safety data sheet in accordance with OSHA final rule on GHS implementation

promulgated March 26, 2012.

Other information : This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29

CFR, 1910.1200. Other government regulations must be reviewed for applicability to this

product.

Full text of H-phrases:

Acute Tox. 3 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 3
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Compressed gas	Gases under pressure Compressed gas
Flam. Gas 1	Flammable gases Category 1
Liquefied gas	Gases under pressure Liquefied gas
H220	Extremely flammable gas
H280	Contains gas under pressure; may explode if heated
H331	Toxic if inhaled
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

SDS US (GHS HazCom 2012)

This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this gas mixture. To the best of Calgaz's knowledge, the information contained herein is reliable and accurate as of this date; however, accruacy, suitability or completeness are not guaranteed and no warranties of any type, either express or implied, are provided. The information contained herein relates only to this specific product. If this gas mixture is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.

03/06/2015 EN (English US) SDS ID: 50006 9/9