

Wet Well Monitor

METHANE • OXYGEN • HYDROGEN SULFIDE
For Hazardous Wastewater Environments

System includes three remote 4-20 mA VDC sensor/transmitters in explosionproof Class I, Div. 1 Group B, C, D enclosures. Specifically designed to monitor CH₄, H₂S & O₂ in wastewater treatment plants.

MONITOR FEATURES

- Digital Display
- User Programmable Alarms
- 2 Alarm Levels per Channel
- Audio/Visual Alarms
- 5 Alarm Relays, plus 1 fault Relay
- 100-240 VAC, 24 VDC Loop Options
- Provides 24 VDC Loop Power
- Designed for 24 VDC Battery Backup
- High Capacity User-Programmable Relays
- High Integrity Thermoplastic Enclosure
- 4-20 mA Output per Channel
- RS-485 Digital Communication Capability



CP-60 3-channel Controller P/N 04651-003

SENSOR/TRANSMITTER FEATURES

- Digital Display
- Non-invasive Calibration
- Explosionproof Sensor/Transmitters
- Magnetically Activated Calibration/Programming Switches
- Alarm LEDs
- Optional Relay PCB



H₂S Sensor
EX-5175
P/N 10014-0200



Methane Sensor
EX-5100
P/N 10014-001



Oxygen Sensor
EX-5175
P/N 10014-1100



Specifications subject to change without notice